

## Horizontal Steam Boiler

## دیگ بخار افقی

MODEL	CAPACITY		Dimension			FULE		Steam outlet(in)
	kg/hr	Lb/hr	L(mm)	W(mm)	H(mm)	Gas(m <sup>3</sup> /hr)	Gas-OIL(l/hr)	
BS-HS01	300	665	1700	1000	1250	20	17	2
BS-HS02	500	1100	2000	1100	1350	28	25	2
BS-HS03	750	1660	2000	1300	1550	36	32	2 1/2
BS-HS04	1000	2210	2300	1500	1800	50	45	2 1/2
BS-HS05	1500	3300	2800	1600	1900	72	69	3
BS-HS06	2000	4400	3200	1800	2150	97	92	3
BS-HS07	2500	5525	3400	1900	2200	125	118	3
BS-HS08	3000	6650	3600	2100	2400	146	137	4
BS-HS09	4000	9000	4000	2100	2500	195	186	4
BS-HS10	5000	11000	5000	2300	2700	255	240	5
BS-HS11	7000	15500	5300	2600	3000	348	335	6
BS-HS12	8500	18800	5600	2700	3200	435	416	8
BS-HS13	10000	22500	6000	2800	3300	528	503	8
BS-HS14	12000	27000	6500	3000	3500	627	600	10
BS-HS15	15000	33200	7000	3200	3800	785	750	10

Approximate consumed fuel and based on torch rest is determined between 15 to 20 min.

All dimensions are approximate only . Refer to engineering dept. for detailed information.