

Domestic Hot Water Generators

منابع کویل دار

MODEL	CAPACITY	Dimension		Heating Surface	Inlet-outlet	Drain	Soft valve
	Lit	H(mm)	D(mm)	(ft2)	(in)	(in)	(in)
BS-DH01	300	1500	500	8	$\frac{3}{4}$	$\frac{1}{2}$	$\frac{3}{4}$
BS-DH02	500	1500	650	15	1	$\frac{3}{4}$	$\frac{3}{4}$
BS-DH03	800	2000	710	20	1 $\frac{1}{4}$	$\frac{3}{4}$	$\frac{3}{4}$
BS-DH04	1000	2000	800	27	1 $\frac{1}{4}$	1	$\frac{3}{4}$
BS-DH05	1500	2000	950	36	1 $\frac{1}{4}$	1	1
BS-DH06	2000	2000	1150	52	1 $\frac{1}{2}$	1	1
BS-DH07	2500	2000	1250	65	1 $\frac{1}{2}$	1	1
BS-DH08	3000	2000	1400	83	1 $\frac{1}{2}$	1	1
BS-DH09	3500	2000	1500	95	2	1	1
BS-DH10	4000	2500	1450	2*55	2 $\frac{1}{2}$	1	1
BS-DH11	5000	3000	1450	2*67	3	1 $\frac{1}{4}$	1 $\frac{1}{4}$
BS-DH12	7000	3000	1720	2*95	3	1 $\frac{1}{2}$	1 $\frac{1}{2}$
BS-DH13	10000	3500	1900	2*135	4	1 $\frac{1}{2}$	1 $\frac{1}{2}$